ELECTRIC TELESCOPIC BOOMLIFT 77738JE

Comply with CE Standard

FEATURES

Standard Features

Horn
Proportional contro;
All motion alarm
Flashing amber beacon
Self-closing entry gate
Emergency lowering system
Emergency stop system
Auto-leveling system
On-board diagnostic system
Over tilt protection system
Oscillating axle
Load sensing system

Accessories & Options

- ▶ Platform light
- ► Anti-collision safety lever
- AC power to platform



HIGHLIGHTS

- ► High-efficiency and energy-saving hydraulic system deadweight lowering technology, saving energy consumption by 23.6%
- ► Safe and reliable lithium battery power system equipped with BMS low-temperature heating and low-temperature charging current control functions improves battery life by 30% and adapts to -20 °C cold environment
- ► Maintenance-free wheel side AC drive system, the maximum gradeability can reach 45%
- ▶ 220V/380V full voltage adaptable charger the three most common charging plugs 10A, 16A, 32A are matched with the matching signal plug on the charging head, can realize charging mode matching and adaptive power for charging

ACCESS WITH ZOOMLION GREEN

Add: 701 Xulong Nan Lu, Xiangjiang New District, Changsha Hunan, China Web: www.zoomlion-access.com

ZOOMLION

Model	ZT38JE				
	Imperial	Metric			
	Size				
Work height	131ft 11in	40.22m			
Platform height	125ft 5in	38.22m			
Horizontal outreach	74ft 3in	22.64m			
A Stowed length	40ft 3in (47ft 1in)	12.26 (14.35) m			
B Stowed width	8ft 2in (12ft 8in)	2.49/3.87m			
C Stowed height	9ft 10in	3m			
D Platform length	8ft	2.44m			
E Platform width	3ft	0.91m			
F Wheelbase	12ft 6in	3.81m			
Tread	8ft 2in (12ft 8in)	2.49/3.87m			
G Ground clearance	1ft 4in	0.41m			
	Performance				
Platform Capacity (Unrestricted/Restricted)	660lb	300kg			
Travel speed (stowed)	3.1mph	5km/h			
Grade ability	45% (24°)	45%			
Turning radius (inside)	10ft 10in/25ft 3in	3.3/7.7m			
Turning radius (outside)	26ft 11in/35ft 5in	8.2/10.8m			
Turntable rotation	360°continuous	360°			
Platform rotation	±90°	±90°			
Tail swing	4ft 10in	1.46			
Jib rotation	-55°~75°	-55°~75°			
Wind speed	28mph	12.5 m/s			
	Power				
Battery	606Ah	606 Ah			
Charger	6kW	6kW			
Drive/Pump motor	30kW	30kW			
Auxiliary power	2kW	2kW			
Hydraulic tank	52.8 (us gal)	200L			
	Tire				
Tire type	Foan	n-filled			
	Weight				
Gross	42328lb	19200kg			





42m										
137ft9in	$\neg \vdash$									
			+		占	1				
36m	\dashv \vdash	+	+-							
118ft1in			+	_//						
30m										
98ft5in				#						
24m				//						
78ft9in										
18m				3	00k	(g/6	60lb	S		
59ft1in										
12m			A							
39ft4in										
6m										
19ft8in		_//								
Om				=	#	=	_			
0in										
VIII										
-6m										
-19ft8in										
	-6m		Om	6	m	1:	2m	18	i Bm	2
	-19ft8		0in	19ft						_

Range of Motion ZT38JE